



Manufacturing options

Trailed AIR-BLAST



- Diaphragm pumps from 80 to 200 l.m. and 40 bars.
- Air-assisted spray head Ø 820 mm, 39 960 m³/hour.
- Air-assisted spray head Ø 915 mm, 48 960 m³/hour.
- Air-assisted spray head VNS fan of Ø 913 mm, 83798 m³/hour.
- Air-assisted spray reverse VNS fan of Ø 913 mm, 83798 m³/hour.
- Air-assisted spray head Ø 1060 mm, 108618 m³/hour.
- Double Air-assisted spray tower x2 Ø 800 mm, 93000 m³/hour.
- Double Air-assisted spray reverse tower x2 Ø 800 mm, 93000 m³/hour.
- Stainless steel groups.
- All stainless steel screws .
- Manual, motorized or solenoid control valves.
- Double nozzle body .
- Modular steel chassis .
- 10.00X14 to 500X15 Wheels .
- Road lighting.
- Hydraulic service brakes .
- Polyethylene tank .
- Washing machine large capacity tank .
- Wash hands tank.
- Mixer with rinsing bottles.
- Distribution tower.
- Deflector for walnut .
- Deflector higher.
- Ultrasonic sensors
- DGPS
- Speed proportional flow

Mounted AIR-BLAST



- Diaphragm pumps from 80 to 110 l.m. and 40 bars.
- Air-assisted spray head Ø 720 mm, 30650 m³/hour.
- Air-assisted spray head Ø 915 mm, 48960 m³/hour.
- Manual, motorized or electronic valves control.
- Double nozzle body .
- Tubular steel chassis .
- Polyethylene tank .
- Cleaning tank.
- Wash hands tank .
- Mixer with rinsing bottles.
- Distribution tower .
- Deflector for walnut .
- Deflector higher.
- All stainless steel screws .
- Ultrasound sensors
- DGPS
- Speed proportional flow



Opcions de fabricació.

Atomitzador arrossegat



- Bombes de membranes de 80 a 200 l.m. i 40 bars.
- Grup ventilador de Ø 820 mm i 39960 m³/hora.
- Grup ventilador de Ø 915 mm i 48960 m³/hora.
- Grup ventilador VNS de Ø 913 mm i 83798 m³/hora.
- Grup ventilador VNS de Ø 913 mm i 83798 m³/hora.
- Grup ventilador de Ø 1060 mm i 108618 m³/hora.
- Grup doble ventilador x2 Ø 800 i 93000 m³/hora
- Grup doble ventilador invers x2 Ø 800 i 93000 m³/hora.
- Grups en acer inoxidable.
- Tots els cargols en acer inoxidable.
- Comandament manual amb electrovàlvules o motoritzat.
- Porta broquets dobles.
- Xassis modular d'acer.
- Rodes de la 10.00X14 a 500X15.
- Enllumenat de carretera.
- Frens de servei hidràulics segons capacitat.
- Dipòsit de polietilè.
- Dipòsit renta màquina de gran capacitat.
- Dipòsit rentamans.
- Incorporador de productes amb renta-envasos.
- Torre de distribució.
- Deflector per noguers.
- Deflector superior.
- Sensors d'ultrasons
- Cabal proporcional a l'avançament
- DGPS



Atomitzador suspès




- Bombes de 50 a 110 l.m. i 40 bars.
- Grup ventilador de Ø 720 mm, 30650 m³/hora.
- Grup ventilador de Ø 915 mm, 48960 m³/hora.
- Comandament manual, amb electrovàlvules o motoritzat.
- Porta broquets dobles.
- Xassis tubular d'acer.
- Dipòsit de polietilè.
- Dipòsit de neteja.
- Dipòsit rentamans.
- Incorporador de productes amb renta envasos.
- Torre de distribució.
- Deflector per noguers.
- Deflector superior.
- Tots els cargols en acer inoxidable.
- Sensors d'ultrasons
- Cabal proporcional a l'avançament
- DGPS





	 Air-Blast	 Air-Blast
A (mm)	Max. 2800	Max. 2800
B (mm)	900 to 1800	2200
C (mm)	1200 to 2200	2000 to 5200
Weight / Pes (kg)	200 to 1000	500 to 2050



Dealer:



AMP Sprayers SL
 Passeig de la Crosa S/N
 17185 Vilobí d'Onyar
 +34 972 47 41 37
 comercial@ampsprayers.com
 ampsprayers.com
 @ampsprayers
 @ampsprayers

Tel. 972 47 41 37

The company reserves the right to modify the characteristics of the machines without notice.
 L'empresa es reserva el dret de modificar les característiques de les màquines sense previ avis.

